



**Dimensions shown with optional 3-way tipping body  
(standard - rear tipping only)**

**Other options available:**

**Power swivel body and high swivel body**

## DIMENSIONS

<i>Trax Carrier</i>		<b>300</b>
Full Length	'A' mm	3160
Full Width	'B' mm	1640
Wheelbase	'C' mm	1955
Min. ground clearance	'D' mm	278
Front overhang	'E' mm	620
Gauge	'F' mm	1250
Track width	'G' mm	350
Vehicle height	'H' mm	1620
Loading height	'I' mm	825
Loading box height	'J' mm	370
Loading box length	'K' mm	1700
Loading box width	'L' mm	1400

## ENGINE

Manufacturer		Kubota
Model		V2203B
Displacement	cc	2197
Power	ps/rpm	46/2800

## HYDRAULICS

Drive system		HST
Max. hydraulic press.	kg/cm <sup>2</sup>	250
Brake system		hydraulic
No. of gears		Low/high

## PERFORMANCE

Machine weight	kg	2200/2500
Max carrying capacity	kg	2500/3000
Tank capacity	litres	52
Speed in low	km/h	6
Speed in high	km/h	9
Climbing ability empty	degrees	30
Ground pressure empty	kg/cm <sup>2</sup>	0.16
Ground pressure laden	kg/cm <sup>2</sup>	0.32

Whilst every effort has been made to give the correct specifications and measurements of every vehicle Morooka Co Ltd and Yuasa Warwick Machinery Ltd cannot be held responsible for the accuracy of the information contained within this brochure.